

# **PRODUCT PARAMETERS**







### Technical Parameters:


Power supply: lithium battery Battery life: Over 3000 times Static current:<70 uA Dynamic current:<2A Storage temperature: -20 - +60℃ Storage temperature: -20 - 400 Storage humidity:10-98% RH Working temperature:-10-+0°C Working humidity:15-98% RH Card reading distance: 0-5cm Reading & writing time: <0.25s
Date keeping:Over 10 years
Reading &writing way:Non-touched closer induction

#### Features:

- 1.Material:Aluminium alloy;
  2.Finish:Satin nickel,antique cooper or gold;
  3.Access mode: fingerprint, password, card, mechanical key;
  4.Fake password prevents your password being peeped;
  5.Low power alarm,Anti-tampering alarm;
  6.System locks for 3mins after 5 continuous wrong input;
  7.Imported PHILIP chip, anti-cloning and high security;
  8.User capacity:500, passwords + cards + fingerprint;
  9.Machanical key unlocking is available for emergency.

- 8. User capacity:500, passwords + cards + lingerprint;
  9. Mechanical key unlocking is available for emergency;
  10. One time password is available;
  11. Voice navigation makes lock setting easy to finish,
  12. With door bell on the lock;
  13.2000 unlocking records can be check,
  14. Automatic unlocking and locked.

# Size



# Mortise







6068 (24\*240mm)

6068 (30\*240mm)

(30/40\*388mm)